

# PROCOOL GLOBAL MV 5050 GREEN MATERIAL SAFETY DATA SHEET

Issue 3 Issue Date: July 2023

## SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### Product Name: PROCOOL GLOBAL MV 5050 GREEN

Company: Recochem Inc. ABN: 69 010 485 999

Address: 1809 Lytton Road, Lytton, Queensland 4178

Phone: (07) 3308 5200

Fax: (07) 3308 5201

**Emergency Telephone Number: Day - (07) 3308 5200 After Hours - 1300 131 001**

Other Names: Glycol Coolant, Antifreeze

Manufacturer's Product Code: 19810

Recommended Use: Radiator Antifreeze, Coolant

## SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA  
NOT A DANGEROUS GOODS ACCORDING TO THE CRITERIA OF THE ADG CODE**

### GHS Classification

Acute Toxicity - Oral Category 4



### Signal Word:

WARNING

### Hazard

H302 - Harmful if swallowed

### Statements:

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure following skin contact and / or if swallowed

### Precautionary

P101 If Medical advice is needed, have product container or label at hand

### Statements:

GENERAL	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
PREVENTATIVE	
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling
P270	Do not eat, drink or smoke when using this product
RESPONSE	
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P330	Rinse Mouth
DISPOSAL	
P501	Dispose of contents/container in accordance with local regulations

# PROCOOL GLOBAL MV 5050 GREEN MATERIAL SAFETY DATA SHEET

Issue 3 Issue Date: July 2023

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Hazardous Ingredients

Chemical Entity	CAS Number	Proportion (%)
Ethylene Glycol	107-21-1	45 - 55

## SECTION 4 FIRST AID MEASURES

### FIRST AID TREATMENT

**Swallowed:** If swallowed, do NOT induce vomiting. Have conscious person drink several glasses of water or milk. SEEK IMMEDIATE MEDICAL ATTENTION.

**Eye:** If in eyes, hold eyes open, flood with water for at least 15 minutes.

If irritation persists seek medical attention.

**Skin:** If skin contact occurs, wash skin thoroughly with water and follow by washing with soap if available.

If irritation persists, seek medical attention.

**Inhaled:** Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

**First Aid facilities:** Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers.

**Advice to Doctor:** Treat symptomatically.

**Additional Information:** None available.

## SECTION 5 FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** For a small fire use dry chemicals, carbon dioxide, water spray or foam.

For large fires use water spray or fog. Do not use water jet.

**Hazards from combustion products:** Carbon dioxide and carbon monoxide.

**Precautions for Fire Fighters and Special Protective Equipment:** Wear full protective clothing and self-contained breathing apparatus.

**Additional Information:** When heated to decomposition, emits acrid smoke and irritating fumes.

Not a product presenting risks of explosion.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

Observe all local and national regulations.

**Spills and Disposal, Methods and Materials for Containment and Clean Up Procedures:** For small spills, dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. For large spills, absorb with an inert material and put the spilled material in an appropriate waste disposal container. Dispose of in accordance with regional regulations.

## SECTION 7 HANDLING AND STORAGE

**Precautions for Safe Handling and Storage:** Avoid contact with eyes, skin and clothing. DO NOT ingest. Avoid breathing vapour and mist, keep container closed. Keep container in a cool, well-ventilated area, away from strong oxidisers, and use only with adequate ventilation. Avoid all possible sources of ignition. Wash thoroughly after handling. Before eating, drinking or smoking, remove contaminated clothing. Do not eat, drink or smoke in contaminated areas.

# PROCOOL GLOBAL MV 5050 GREEN MATERIAL SAFETY DATA SHEET

Issue 3 Issue Date: July 2023

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Standards:** National Occupational Health & Safety Commission (NOHSC) Worksafe Australia has set an exposure standard of 52mg/m<sup>3</sup> (20ppm) TWA (vapour), 104mg/m<sup>3</sup> (40ppm) STEL (vapour) and 10mg/m<sup>3</sup> TWA (particulate).

**Biological Limit Values:** No biological limit allocated.

### Personal Protective Equipment

**Respiratory Protection:** Wear appropriate respirator when ventilation is inadequate.

**Hand Protection:** Use solvent resistant gloves (nitrile, PVC or neoprene).

**Eye Protection:** Wear safety goggles.

**Protective Clothing:** No special protection is ordinarily required beyond standard issue work clothes.

**Engineering Controls:** Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DESCRIPTION	CHEMICAL PROPERTIES
Appearance	Green viscous liquid
Odour	None
pH	7.8 to 9.5
Vapour Pressure (mmHg @ 20°)	0.06
Vapour Density (air = 1)	2.1
Boiling Point (°C)	121 - 132
Freezing/Melting Point (°C)	-37
Solubility in Water	Soluble in water, methanol, diethyl ether
Specific Gravity (g/ml @ 15°C)	1.05 - 1.12
Flashpoint (°C)	Not available
Flammability Limits (%)	Not available
Auto Ignition Temperature (°C)	Not available

## SECTION 10 STABILITY AND REACTIVITY

**Chemical Stability:** Stable under normal conditions of use.

**Conditions to Avoid:** No additional remark.

**Incompatible Materials:** Strong oxidising agents, acids, alkalis.

**Hazardous Decomposition Products:** Burning can produce carbon monoxide and/or carbon dioxide.

## SECTION 11 TOXICOLOGICAL INFORMATION

### HEALTH EFFECTS

#### Acute:

**Swallowed:** Hazardous in case of ingestion (approx. 100ml can be fatal).

**Eye:** Contact may cause eye irritation.

**Skin:** Irritant – prolonged contact may cause dermatitis.

**Inhaled:** Inhalation should be minimal since vapours are unlikely due to physical properties.

Inhalation may cause irritation to lung.

**Chronic:** Toxic to kidneys and liver.

**Toxicity to Animals:** Acute oral toxicity (LD50): 4700mg/kg (Rat).

Acute dermal toxicity (LD50): 9530 mg/kg (Rabbit).

# PROCOOL GLOBAL MV 5050 GREEN MATERIAL SAFETY DATA SHEET

Issue 3 Issue Date: July 2023

## SECTION 12 ECOLOGICAL INFORMATION

### Ecotoxicity:

Fish: Low toxicity: LC/EC/IC50 > 100mg/l

Aquatic Invertebrates: Low toxicity: LC/EC/IC50 > 100mg/l

Algae: Low toxicity: LC/EC/IC50 > 100mg/l

Microorganisms: Low toxicity: LC/EC/IC50 > 100mg/l

**Mobility:** Miscible with water.

**Persistence/degradability:** Biodegradable.

## SECTION 13 DISPOSAL CONSIDERATIONS

**Disposal Methods:** Ensure waste disposal conforms to local waste disposal regulations.

## SECTION 14 TRANSPORT INFORMATION

**UN Number:** Non Regulated

**Class:** N/A

**Packing Group:** N/A

**Special Precautions for User:** None

**Proper Shipping Name:** N/A

**Subsidiary Risk:** N/A

**Hazchem Code:** N/A

## SECTION 15 REGULATORY INFORMATION

**Poisons Schedule:** 5

**AICS:** Listed

**Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76:2010):** N/A

## SECTION 16 OTHER INFORMATION

Further Information may be obtained by contacting Recochem on (07) 3308 5200.

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product.